



TECHNICAL DATA SHEET

SHORT DESCRIPTION:

OSI Reclaiming Powder dissolves into water to create a liquid emulsion remover. This is a powerful concentrate that can be mixed into many ratios ranging from extremely powerful to your every-day reclaiming liquid.

OSI RECLAIMING POWDER BENEFITS:

- Low cost per gallon.
- Lower shipping weight compared to liquid emulsion removers.
- Different mixing ratios allow for stronger/weaker solution.
- Easy to mix in large or small quantities.

MIXING INSTRUCTIONS:

- Standard ratio: 2 oz. OSI Reclaiming Powder to 1 gallon of water.
- For a powerful solution, add 1 lbs. OSI Reclaiming Powder to 5 gallons of water.
- Stir until all of the white powder has dissolved into the water.

EMULSION REMOVAL INSTRUCTIONS:

1. Add the solution to a spray bottle.
2. Spray the front and back of the screen.
3. Scrub both sides with a chemical resistant scrub pad.
4. Pressure wash both sides of the screen until the emulsion is completely removed.

Important note: Never allow any emulsion remover to dry on the screen. This will lock-in the emulsion.

Always perform a pretest print and test cure conditions on the fabric to be printed to establish the best results. Stir inks vigorously before each use. Viscosity may need adjusting for best results. If there is ever a question about a print job, call us at 800-942-4447. We are always happy to help!